

J3.91

Optics:

Pixel Pitch	3.91mm
Pixel Configuration	SMD2427 Blackface
Brightness	1000-1400 nit
Resolution	128 x 128
Pixel Density	16,384 Pixels Per Panel
Best Viewing Distance	> 3m (9.8 ft)
Horizontal Viewing Angle	> 140
Vertical Viewing Angle	> 120
Contrast Ratio	4000:1
Blind Spot Rate	< 0.00001
Color Temperature	6500k - 9500k
Module Configuration	8pcs
Screen Life Span	> 100,000 Hrs

Control:

Drive Mode	1/16
Data In/Out	Network in + Out
IC	MacroBlock MBI5252
Refresh Rate	≥ 3840 Hz
Grey Scale	16 bit
Brightness Adjustment	256 grade automatic, 8 grade manual
Exchange Frame Rate	> 60 frames/second

Specifications:

Panel Dimensions	500mm x 500mm x 88mm (19.7in x 19.7in x 3.5in)
Module Dimensions	250mm x 125mm (9.8in x 4.9in)
Gap Between Panels	< 0.3mm
Weight	21 lbs
Power Connection	Powercon In + Out
Power Supply	100-240V 50/60Hz
Average Power Consumption	75W
Max Power Consumption	150W
Max Heat Load	512 BTU/Hr
Working Environment Temperature	-20C~+50C (-4F ~ 122F)
Working Environment Humidity	10%~60%
IP Rating	IP30