

JX2.53

Optics:

Pixel Pitch	2.53mm
Pixel Configuration	SMD2020 Blackface
Brightness	800-1300nits
Resolution	135 x 240 pixel
Pixel Density	32400 Pixels Per Panel
Best Viewing Distance	≥ 2 m (6.6Ft)
Horizontal Viewing Angle	> 160
Vertical Viewing Angle	> 140
Contrast Ratio	5000:1
Blind Spot Rate	< 0.00001
Color Temperature	6500k - 9500k
Module Configuration	4pcs
Screen Life Span	> 100,000 Hrs

Control:

Drive Mode	1/27
Data In/Out	Network In + Out
IC	MacroBlock MBI5153
Refresh Rate	≥ 3840 Hz
Grey Scale	16 bit
Brightness Adjustment	Manual
Exchange Frame Rate	> 60 frames/second

Specifications:

Panel Dimensions	13.5"x 23.9"x 2.9" (342mm x 608mm x 73mm)
Module Dimensions	342mm x 152mm (13.46in x 5.98in)
Gap Between Panels	< 0.3mm
Weight	17.64 lbs
Power Connection	Powercon In + Out
Power Supply	100-240V 50/60Hz
Average Power Consumption	75W
Max Power Consumption	150W
Max Heat Load	518 BTU/Hr
Working Environment Temperature	-20C~+50C (-4F ~ 122F)
Working Environment Humidity	10%~60%
IP Rating	IP 30